

DFWLKI 3GD

"DFWLKI3GD": MULTIFUNCTION WEIGHT INDICATOR FOR ATEX 2 & 22 ZONES



Easy to programme and use, versatile and high performing weight indicator, with IP68 stainless steel case. Ideal for using in areas classified as hazardous with protection methods according to
II 3G Ex nR IIC T6 Gc X for gases
II 3D Ex tc IIIC T130°C Dc IP68 X for dust.
CE-M approvable (OIML R-76/EN 45501).

**The best solution
for advanced industrial
applications**

MAIN FEATURES:

- Waterproof 17-key numeric-functional keypad.
- LCD 25mm backlit display with 6 high contrast digits and icons for indication of active functions.
- Waterproof IP68 STAINLESS STEEL case, with sealed rubber gasket, easy to clean and resistant in harsh and corrosive environments.
- Dimensions in mm: 243x145x78,4 mm.
- Suitable for use on the table, column, or wall.
- A/D 24 bit converter, 4 channels, up to 200 conv./sec. autoselect and up to 8 signal linearisation points.
- Up to 10.000e or multirange 3 x 3000e @ 0,3 $\mu\text{V/d}$ in CE-M approved version for legal for trade use.
- Up to 1.000.000 displayable divisions with built-in resolution up to 3.000.000 points.
- Connection with up to 8 load cells with input resistance equal to 350 Ohm or up to 16 cells of 700 Ohm each.
- Digital calibration and set-up from keypad or from PC with DINITOOLS.
- Power supply:
 - DFWLKI 3GD: through 110-240Vac internal power adapter;
 - DFWLKI 3GDB: through optional external battery (BP6ESTATEX3GD code), rechargeable in safe area.

MAIN CERTIFICATIONS

- EU Type Examination Certificate (45501:2015)
- OIML R76

FUNCTIONS:

- KEYBOARD:
 - Zeroing, Automatic tare, Presetable tare, printing and/or data transmission, selectable function command, on/off switching, database of 30 tares, 2 numeric IDs, keyboard lock, repetition of last printout made.
- SELECTABLE FUNCTIONS:
 - High Resolution Weighing x 10.
 - Net/Gross or lb/kg conversion.
 - Accumulation.
 - Formula weighing.
 - +/- Checkweighing.
 - Percentage weighing.
 - Approved transmission of the weight to PC/PLC (with Alibi memory ALMEM option).
 - Counting (Max. resolution of 1.500.000 divisions).
 - In/Out Truck weighing.
 - Hold and Peak.

I/O SECTION

- RS232/C bidirectional port for connection to PC in safe zone.
- RS232/C bidirectional port for connection to printer or labeller in safe zone.

MASTER/REPEATER OPTION

- Specific programme (MSTSLV code) for use of the indicator as a universal weight repeater or as a multi-scale repeater (MASTER) in combination with DFW/DGT/MCW.

FUNCTIONING MODES:

- Multi-scale repeater (MASTER)
function which allows to repeat up to 32 independent scales, with the possibility of managing their functions, or displaying and printing the sum of the weighs of all the scales.
- UNIVERSAL weight repeater
function which allows to repeat the weight of any scales, through the configuration of the input string.
- [Click to learn more.](#)



DINI ARGEO
FRANCE sarl
France

DINI ARGEO
GMBH
Germany

DINI ARGEO
UK Ltd
United Kingdom

DINI ARGEO WEIGHING
INSTRUMENTS Ltd
China

DINI ARGEO
OCEANIA
Australia



COMPANY HEADQUARTERS

Via Della Fisica, 20
41042 Spezzano di Fiorano Modena • Italy
Tel. +39.0536 843418

SERVICE ASSISTANCE

Via Dell'Elettronica, 15
41042 Spezzano di Fiorano Modena • Italy
Tel. +39.0536 921784

SALES AND TECHNICAL ASSISTANCE SERVICE