

ES

"ES" SERIES 4-CELL PLATFORMS, 600x600mm SIZE



Monobloc electronic platforms, fitted with stainless steel bending beam load cells. Suitable for weighing in all types of industrial and commercial applications. Standard version is with approved load cell.

MAIN FEATURES

- Fitted with 4 bending beam, stainless steel, approved load cells with IP68 protection from dust and water.
- Very sturdy monobloc structure with fixed sheet-steel chequered loading surface.
- IP68 junction box.
- Oven-fire painted RAL 5007 blue.
- Adjustable, antislip feet and level.
- Up to 15 Vdc power supply.
- 5 m 6-pin shielded cable, complete with female connector.


OPTIONS ONLY AVAILABLE AT TIME OF ORDER

- Connection to the indicator and calibration with CE-M 3000e single range or 3000e+3000e dual range approval.
- Models with special sizes and capacities (ask for estimate).

ACCESSORIES

- Indicator support stand.
- Pit frame for flush floor installation.

CONNECTOR PINOUT



Pin	Signal	Color	
1	EXC+	Brown	
2	EXC-	Grey	
3	SENSE-	White	
4	SENSE+	Green	
5	SIG-	Yellow	
6	SIG+	Pink	
7		Not connected	

VERSIONS

Available version	าร						
	lxwxh	N° celle	Max	d	M	M	d HR
Codice	(mm)	N Celle	(kg)	(g)	(g)*	2R (g)*	(g)*
ES150-1	600x600x88	4x100kg	150	20	50	20-50	5
ES300-1	600x600x88	4x200kg	300	50	100	50-100	10

^(*) Divisions obtainable only with the relative options, in combination with Dini Argeo weight indicator.





DINI ARGEO FRANCE sarl France DINI ARGEO GMBH Germany

DINI ARGEO UK Ltd United Kingdom DINI ARGEO WEIGHING INSTRUMENTS Ltd China DINI ARGEO OCEANIA Australia



COMPANY HEADQUARTERS

Via Della Fisica, 20 41042 Spezzano di Fiorano Modena - Italy Tel. +39.0536 843418

SERVICE ASSISTANCE

Via Dell'Elettronica, 15 41042 Spezzano di Fiorano Modena - Italy Tel. +39.0536 921784

-	
	SALES AND TECHNICAL ASSISTANCE SERVICE