

OBWIFI3GD\_OLD20190117

"OBWIFI3GD": WIFI INTERFACE BOX  
FOR ATEX 2 and 22 ZONES



WiFi module for the wireless data communication in ATEX 2 and 22 zones, with protection methods according to:  
ATEX II 3G Ex ec IIB T6 Gc X for gases  
ATEX II 3D Ex tc IIIC T85°C Dc IP66 X for dust.  
It can be applied to both bench/floor scales as well as mobile scales, such as pallet truck scales or pallet weighing scales. It allows the easy wireless connection to the company computer system and the data transmission at a very long distance.

**The best solution  
for advanced industrial  
applications**

## Technical features

- IP66 ABS case.
- Dimensions case (lxwxh): 122x120x65mm.
- Fitted with 3m shielded cable, for connection to the indicator.
- Power supply directly from the indicator.

## Operating features

- Range:
  - external: 70 m
  - internal: 30 m. This distance can change depending on where it is used: greater the hostility of the environment and less is the reachable distance.
- Frequency: 2.4 GHz.
- Data Rate: up to 11 Mbps with automatic fallback.
- Protocols and functioning modes: those foreseen by the IEEE 802.11b, including WEP (cryptography).
- Operating temperature: -20°C +85°C.



[www.diniargeo.com](http://www.diniargeo.com)

“YOUR WORLDWIDE PARTNER FOR WEIGHING,”

DINI ARGEO  
FRANCE sarl  
France

DINI ARGEO  
GMBH  
Germany

DINI ARGEO  
UK Ltd  
United Kingdom

DINI ARGEO WEIGHING  
INSTRUMENTS Ltd  
China

DINI ARGEO  
OCEANIA  
Australia



#### COMPANY HEADQUARTERS

Via Della Fisica, 20  
41042 Spezzano di Fiorano Modena • Italy  
Tel. +39.0536 843418

#### SERVICE ASSISTANCE

Via Dell'Elettronica, 15  
41042 Spezzano di Fiorano Modena • Italy  
Tel. +39.0536 921784

SALES AND TECHNICAL ASSISTANCE SERVICE