

LTFPRO

LTF "PROFESSIONAL" SERIES WEIGHING KIT FOR LIFT TRUCK FORKS



Pair of forks with an integrated weighing system, for lift trucks; easy to use, sturdy, and reliable. The indicator installable in the cabin eases the weighing operations, and can be fitted with a wide range of accessories. Functions through rechargeable battery or through direct powering from the lift truck.

Compatible with any lift truck having a DIN 15173 - FEM fork holder plate, of the IIA (IIB optional) or IIIA class. Available CE-M approved.

**The best solution
for advanced industrial
applications**

MAIN FEATURES

- Weight indicator in cabin with 17-key numerical/functional waterproof keypad, LCD backlit display with 6 high contrast 25-mm digits and easy to clean Waterproof IP65 ABS case resistant to harsh and corrosive environments. Integrated radio module, for communication with the weighing forks.
- Second weight indicator, attached to the forks, with 5-key numerical/functional waterproof keypad, LCD backlit display with 6 high contrast 25-mm digits protected in thick steel case. Integrated radio module, for communication with the indicator in cabin.
- Structure of the forks in painted steel with IP65 protection degree.
- Each fork weighs 75 kg (LTF25) and 90 kg (LTF50).
- Functions with 4 shear-beam IP68 load cells
- Accuracy: +/- 0.2% of the capacity
- Max. allowable overload: 200% of the nominal capacity.
- Max. horizontal inclination (flexibility): +/- 2° with the same precision features.
- Digital calibration and set-up through keyboard or PC with DINITOOLS.
- Forks power supply through rechargeable battery, 40-hour approximate operating time
- Indicator in cabin power supply through rechargeable battery (40-hour approximate operating time) or directly from the lift truck through optional power adapter.
- Programmable auto power saving function.
- Equipped with battery charger.

KEYBOARD FUNCTIONS AND PRINTOUT

- KEYBOARD: clearing, semi automatic tare, presettable tare, print and/or data transmission, selectable function command, on/off.
- PRINTOUT: customisable print layout.

OPTIONS ONLY AVAILABLE AT TIME OF ORDER




- Thermal printer option box.
- Time/Date.

SELECTABLE FUNCTIONS

- High Resolution Weighing x 10
- Net/Gross or lb/kg conversion
- Weighs totalisation
- Formulation
- +/- Check
- Percentage weighing
- Counting
- Hold and Peak

VERSIONS

Available versions

Codice	Piastra	Max (kg)	d (kg)	 (kg)
LTF1125AR-2	FEM2A	500 / 1000 / 2500	1 / 2 / 5	--
LTF1125ARM-2 	FEM2A	1000 / 2500	--	2 / 5
LTF1150AR-2	FEM3A	1000 / 2500 / 5000	2 / 5 / 10	--
LTF1150ARM-2 	FEM3A	2500 / 5000	--	5 / 10



www.diniargeo.com

“YOUR WORLDWIDE PARTNER FOR WEIGHING,”

DINI ARGEO
FRANCE sarl
France

DINI ARGEO
GMBH
Germany

DINI ARGEO
UK Ltd
United Kingdom

DINI ARGEO WEIGHING
INSTRUMENTS Ltd
China

DINI ARGEO
OCEANIA
Australia



COMPANY HEADQUARTERS

Via Della Fisica, 20
41042 Spezzano di Fiorano Modena • Italy
Tel. +39.0536 843418

SERVICE ASSISTANCE

Via Dell'Elettronica, 15
41042 Spezzano di Fiorano Modena • Italy
Tel. +39.0536 921784

SALES AND TECHNICAL ASSISTANCE SERVICE