DINI ARGEO

A RICE LAKE WEIGHING SYSTEMS COMPANY

LP542S

LP542S DIRECT THERMAL LABELLER



Direct thermal labeller with fitted front peel mechanism with label present sensor; it is connectable to DFW, TRI, 3590, and TRS series' indicators.
The fast label throughput, the high printing resolution and the compact size make it suitable for printing in any industrial environment.

The best solution for advanced industrial applications

TECHNICAL FEATURES

- PRINTING METHOD: Direct thermal.
- PRINTING RESOLUTION: 203 dpi (8 dots/mm).
- PRINT SPEED: up to 127 mm/sec.
- MAXIMUM PRINT LENGTH: 1016 mm.
- MAXIMUM PRINT WIDTH: 108 mm.
- LABEL LENGTH: From 10 mm up to 999 mm.
- LABEL WIDTH: From 20 mm up to 112 mm.
- LABEL THICKNESS: From 0.06 mm up to 0.19 mm.
- LABEL ROLL DIMENSIONS: 127 mm OD (5.0" OD).
- FONTS: 8 fixed alphanumeric fonts, 1 true type Font with rotation at 0, 90, 180, and 270 degrees.
- AVAILABLE BAR CODES: Code 39, Code 39C, Code 93, Code 128uCC, Code 128 (Subset A, B, C), Codabar, Interleave 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN e UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China Post, ITF 14, EAN14.
- AVAILABLE 2D BAR CODES: PDF-417, MAXICODE, DATA MATRIX, QR code.
- MEMORY: 2 MB DRAM, 2 MB Flash Memory.
- INTERFACES: RS 232, Parallel, USB 1.1.
- STANDARD SOFTWARE PROGRAMMING, for the creation of customised labels with logos, images, weight data, and bar codes.
- DIMENSIONS: 240 X 200 X 164 mm.
- POWER SUPPLY: Switching 100/240 VAC, 24V 3.75A DC (external power adapter).
- OPERATING TEMPERATURE: From 5 to 40°C.

DETAIL 1



www.diniargeo.com



DINI ARGEO FRANCE sarl	DINI ARGEO GMBH	DINI ARGEO UK Ltd	DINI ARGEO WEIGHING INSTRUMENTS Ltd	DINI ARGEO OCEANIA
France	Germany	United Kingdom	China	Australia

DINI ARGEO
A RICE LAKE WEIGHING SYSTEMS COMPANY

COMPANY HEADQUARTERS
Via Della Fisica, 20
41042 Spezzano di Fiorano Modena • Italy
Tel. +39.0536 843418

SERVICE ASSISTANCE
Via Dell'Elettronica, 15
41042 Spezzano di Fiorano Modena • Italy
Tel. +39.0536 921784

SALES AND TECHNICAL ASSISTANCE SERVICE

All the specifications and images can be subject to variations and upgrades without prior notice.