

## CP

## CP SERIES LOW PROFILE LOAD CELLS



Stainless steel compression load cells suitable for weighing tanks and hoppers with the relevant accessories.

**CAPACITIES (kg)**: 250, 500, 1000, 2500, 7500, 15000, 50000.

**Stainless** steel. **IP68** protection. **C3** precision class.

### **MAIN FEATURES**

- LOW PROFILE
- STAINLESS STEEL CONSTRUCTION
- IP68 PROTECTION
- MAX. CAPACITIES FROM 250 TO 100000 kg
- SHIELDED CONNECTION CABLE

### **TECHNICAL FEATURES**

• Full Scale Output: 2mV/V +/- 0,5%

• Non-Repeatability: 0,01% F.S.

• Temperature effect on zero: 0,02% / 10°C

• Temperature effect on full scale output: 0,02% / 10°C

• Compensated Temperature Range: -10°C/+50°C

• Operating Temperature Range: -20°C/+60°C

• Creep error after 30 minutes: 0,02% F.S.

• Recommended excitation voltage: 10 Vdc

• Maximum tolerated excitation voltage: 15 Vdc

Input Resistance: 750 ± 10 Ohm
Output Resistance: 700 ± 5 Ohm

• Zero Balance: +/-1% F.S.

• Insulation Resistance: >5000 MOhm

• Safe Overload: 120% F.S.

• 4-wire shielded cable, 5 mm diameter:

- 5 m long for CP 250...5000 versions;

- 10 m long for CP 7500...100000 versions.

| Wii    | ring Code       |
|--------|-----------------|
| Colour | <u>Function</u> |
|        | SHIELD          |
| GREEN  | OUTPUT +        |
| RED    | INPUT +         |
| WHITE  | OUTPUT -        |
| BLACK  | INPUT -         |

### **ATEX VERSION**

• The CCATEX certificate makes the load cell suitable for use in hazardous areas with protection methods according to:

ATEX II 1G Ex ia IIC T6 (Ta -20÷+40°C) TX (Ta -20÷+65°C) Ga

ATEX II 1D Ex ta IIIC TX°C (Ta -20÷+40°C) TX°C (Ta -20÷+65°C) Da IP65.

The certificate includes the manual and the ATEX CE conformity declaration (available in EN, DE, FR, and IT).

• IMPORTANT: the certificate refers to the single load cell. For systems with more load cells, it is necessary to order one certificate for each load cell.

# VERSIONS

| Available versions |       |
|--------------------|-------|
|                    | Max   |
| Codice             | (kg)  |
| CP250              | 250   |
| CP500              | 500   |
| CP1000             | 1000  |
| CP2500             | 2500  |
| CP7500             | 7500  |
| CP10000            | 10000 |
| CP15000            | 15000 |





DINI ARGEO FRANCE sarl France DINI ARGEO GMBH Germany

DINI ARGEO UK Ltd United Kingdom DINI ARGEO WEIGHING INSTRUMENTS Ltd China DINI ARGEO OCEANIA Australia



#### **COMPANY HEADQUARTERS**

Via Della Fisica, 20 41042 Spezzano di Fiorano Modena - Italy Tel. +39.0536 843418

#### SERVICE ASSISTANCE

Via Dell'Elettronica, 15 41042 Spezzano di Fiorano Modena - Italy Tel. +39.0536 921784

| - |  |
|---|--|
|   |  |
|   |  |
|   |  |
|   | SALES AND TECHNICAL ASSISTANCE SERVICE |