

STU-1K

"STU-1K": Tension/Compression load cells



Tension/Compression <u>load cells</u>, suitable for weighing in tension suspended loads and as overload checking and limitation, or for compression use in the creation of weighing systems with various load cells.

CAPACITIES (kg): 2000, 5000, 8000, 10000.

OIML R60. C3 precision class.

Stainless steel. IP68 protection.

MAIN FEATURES

- C3 PRECISION CLASS
- STAINLESS STEEL CONSTRUCTION
- IP68 PROTECTION LEVEL
- MAX. CAPACITIES FROM 2000 TO 10000 kg
- 3m SHIELDED CONNECTION CABLE

TECHNICAL FEATURES

• nLC: 3000

• Y: 12000(compression, Y=Emax/Vmin)

• Y: 9500(tension, Y=Emax/Vmin)

• Cn: 2,4 mV/V

Input: 1000 +/- 20 Ohm
Output: 1000 +/- 5 Ohm
Excitation: 1...10Vdc
Safe Overload: 120%

• 6-wire shielded cable, 3 m long, 5mm diameter

MAIN CERTIFICATIONS

- OIML R60
- Australian legal for trade certificate of approval (NMI S840)

DETAIL 1



Dimensions (mm)

Wiring Code	
Colour	<u>Function</u>
METAL	SHIELD
YELLOW	OUTPUT +
GREY	SENSE +
BROWN	INPUT +
WHITE	OUTPUT -
PINK	SENSE -
GREEN	INPUT -

VERSIONS

Available versions	
	Max
Codice	(kg)
STU2000-1KD	2000
STU5000-1KD	5000
STU8000-1KD	8000
STU10000-1KD	10000





DINI ARGEO FRANCE sarl France DINI ARGEO GMBH Germany

DINI ARGEO UK Ltd United Kingdom DINI ARGEO WEIGHING INSTRUMENTS Ltd China DINI ARGEO OCEANIA Australia



COMPANY HEADQUARTERS

Via Della Fisica, 20 41042 Spezzano di Fiorano Modena - Italy Tel. +39.0536 843418

SERVICE ASSISTANCE

Via Dell'Elettronica, 15 41042 Spezzano di Fiorano Modena - Italy Tel. +39.0536 921784

-	
	SALES AND TECHNICAL ASSISTANCE SERVICE