DINI ARGEO

A RICE LAKE WEIGHING SYSTEMS COMPANY

EPI_OLD20191122

MULTIFUNCTION, STAINLESS STEEL, MODULAR WEIGHING SOLUTIONS



Simples and economics, modular weighing solutions.
The DFWKXT weight indicator offers a stainless steel case, a built-in rechargeable battery with very long life, and many selectable functions, which allow to totalize the executed weighs, count pieces, activate relay outputs (in option), and print tickets complete with header.
The completely AISI304 stainless steel platform is suitable also for environments with strict hygiene requirements. The EasyPesa systems are available in legal for trade approved version.

The best solution for advanced industrial applications

MAIN FEATURES

- DFWKXT series weighing indicator:
  - Easy to clean STAINLESS STEEL waterproof IP68 enclosure.
  - LCD backlit display with high contrast digits.
  - 17-key numerical and functional waterproof keypad.
  - Built-in rechargeable battery (60 hours with one 350-Ohm load cell) and 110-240 Vac internal power adapter.

- TE series - single cell platform:
  - Structure with tubulars, mechanics, trinkets and loading surface in AISI304 satin finish stainless steel.
  - Adjustable feet and level.

MAIN FUNCTIONS

- KEYBOARD:
  Zeroing, Automatic tare, Presettable tare, printing and/or data transmission, selectable function command, on/off switching, database of 10 tares, 2 Numeric IDs, keyboard lock, repetition of last printout made.

- SELECTABLE FUNCTIONS:
- High resolution visualization x 10, useful to view the weight with a sensitivity 10 times greater.
- Net/Gross conversion, it means the possibility to switch between the displaying of the net weight to the gross weight by pushing a button, when a tare is active.
- kg/lb conversion with the print of a receipt in both the two units.
- Horizontal accumulation: sum fo more successive weighs and print of the total.
- Formula weighing: manual mixing of various consecutive products according to the formula or loading of the pallet with various products and print of the total.
- +/- tolerance checking, to verify if the weight is within the desired limits.
- Percentage weighing, it means the displaying of the weight percentage on the scale compared with the configured 100%.
- Approved transmission of the weight to PC/PLC or data recording on MMC/USB (with Alibi memory ALMEM option).
- Simple pieces counting, with entry of the reference quantity or of the average unit weight.
- Hold, manual freezing of the weight on display.
- Set Point Control (with DFIO option), on the net or gross weight, with programmable thresholds. When the threshold is reached, the correspondent relay is activated / deactivated.
- Printouts with customizable header.

VERSIONS

Available versions

Codice	l x w x h (mm)	Max (kg)	d (g)	M (g)*	M 2R (g)*	d HR (g)*
TTE6	330x330x90	6	1	2	1-2	0,5
TTE15	330x330x90	15	2	5	2-5	1
TTE30	330x330x90	30	5	10	5-10	2
TQE30	400x400x115	30	5	10	5-10	2
TQE60	400x400x115	60	10	20	10-20	5
TQE150	400x400x115	150	20	50	20-50	10
TXE60	600x600x137	60	10	20	10-20	5
TXE150	600x600x137	150	20	50	20-50	10
TXE300	600x600x137	300	50	100	50-100	20

(*) These divisions are obtainable only with the relative options

www.diniargeo.com



DINI ARGEO FRANCE sarl	DINI ARGEO GMBH	DINI ARGEO UK Ltd	DINI ARGEO WEIGHING INSTRUMENTS Ltd	DINI ARGEO OCEANIA
France	Germany	United Kingdom	China	Australia

DINI ARGEO
A RICE LAKE WEIGHING SYSTEMS COMPANY

COMPANY HEADQUARTERS
Via Della Fisica, 20
41042 Spezzano di Fiorano Modena • Italy
Tel. +39.0536 843418

SERVICE ASSISTANCE
Via Dell'Elettronica, 15
41042 Spezzano di Fiorano Modena • Italy
Tel. +39.0536 921784

SALES AND TECHNICAL ASSISTANCE SERVICE

All the specifications and images can be subject to variations and upgrades without prior notice.