

PLK

"PLK-1" SERIES' 350 Ohm LOAD CELL KITS FOR ASSEMBLING FLOOR SCALES



Ideal for creating platforms with 4 load cells of various sizes and capacities. The kit is made up of 4 350 Ohm IP68 stainless steel load cells, OIML approved, together with adjustable stainless steel resting feet and an equalisation box.

LOAD CELL TECHNICAL FEATURES

- C3 precision class
- Stainless steel construction with laser weldings
- IP68 protection
- Max. Capacities from 300 to 2000 kg (for each load cell)
- Minimum load cell verification interval: Vmin = EMax / 10.000
- Maximum number of verification intervals: nLC = 3000
- Combined error: 0,017% of Full Scale Output (F.S.)
- Full Scale Output: 2mV/V +/- 0.1%
- Temperature effect on zero: 0,0014% /°C
- Temperature effect on full scale output: 0,0014% /°C
- Compensated Temperature Range: -10°C/+40°C
- Operating Temperature Range: -20°C/+60°C
- Creep error after 30 minutes: 0,024% F.S.
- Maximum tolerated excitation voltage: 15 Vdc
- Input Resistance: 385 ± 20 Ohm
 Output Resistance: 350 ± 5 Ohm
- Insulation Resistance: >5000 MOhm
- Safe Overload: 150% F.S.
- Ultimate Overload: 200% F.S.
- 6-wire shielded cable, 5m long, 5 mm diameter

RESTING FEET

- Adjustable in height
- Structure in STAINLESS steel
- Anti-slip base
- Ipersanitizable
- Fitted with locking bush

JUNCTION BOX

- Built-in junction and equalisation board
- IP67 protection from dust and water
- 5 PG9 Fairleads

IN +	BROWN
IN -	GREEN
SIG (OUT) +	YELLOW
SIG (OUT) -	WHITE
SENSE+	GRAY
SENSE -	ROSE
SHIELD	METAL





DINI ARGEO FRANCE sarl France DINI ARGEO GMBH Germany

DINI ARGEO UK Ltd United Kingdom DINI ARGEO WEIGHING INSTRUMENTS Ltd China DINI ARGEO OCEANIA Australia



COMPANY HEADQUARTERS

Via Della Fisica, 20 41042 Spezzano di Fiorano Modena - Italy Tel. +39.0536 843418

SERVICE ASSISTANCE

Via Dell'Elettronica, 15 41042 Spezzano di Fiorano Modena - Italy Tel. +39.0536 921784

-	
	SALES AND TECHNICAL ASSISTANCE SERVICE