

FLI

STAINLESS STEEL PLATFORM "FLOOR" FLI SERIES



Double range STAINLESS steel <u>platform</u>, with approved STAINLESS load cells, suitable for weighing application in industry and any commercial environment. IP68 protection.

STAINLESS PLATFORMS: TECHNICAL FEATURES

- Functioning with 4 STAINLESS steel shear-beam load cells (1000 ohm), OIML R60 C3 approved (3000 divisions), IP68 protection degree.
- Monobloc structure in STAINLESS steel, adjustable resting feet and level.
- Fixed STAINLESS steel load surface.
- Max. Power supply 15 Vdc.
- Hermetic junction box, with IP67 protection or IP68 (if integrated with the GELBOX option).
- 3m shielded cable for the connection with the indicator.
- IP68 Watertight connector.

STAINLESS PLATFORMS: OPTIONS

- Connection to the indicator and configuration/calibration at our office.
- Connection to the indicator and calibration with single scale 3000e or double scale 3.000 + 3.000e CE-M approval.
- Support column for the indicator.

DETAIL 1

DETAIL 2



VERSIONS

Available version	IS					
	lxwxh	N° celle	Max	d	M	M
Codice	(mm)	N Cene	(kg)	(g)	(g)*	2R (g)*
FLBI1500	1250x1250x120	4x1000kg	600/1500	200/500	500	200/500





DINI ARGEO FRANCE sarl France DINI ARGEO GMBH Germany

DINI ARGEO UK Ltd United Kingdom DINI ARGEO WEIGHING INSTRUMENTS Ltd China DINI ARGEO OCEANIA Australia



COMPANY HEADQUARTERS

Via Della Fisica, 20 41042 Spezzano di Fiorano Modena - Italy Tel. +39.0536 843418

SERVICE ASSISTANCE

Via Dell'Elettronica, 15 41042 Spezzano di Fiorano Modena - Italy Tel. +39.0536 921784

-	
	SALES AND TECHNICAL ASSISTANCE SERVICE