
DINI ARGEO

A RICE LAKE WEIGHING SYSTEMS COMPANY

ETI_INOX_C6

ETI SERIES 4-C6 CELLS STAINLESS STEEL PLATFORMS



C6

Electronic STAINLESS STEEL AISI 304 weighing low profile platforms with removable loading plate fitted with IP68 STAINLESS STEEL C6 approved load cells. Suitable for creating scales and electronic weighing systems for all types of industrial and commercial applications. Available in high resolution and suitable for ATEX zones.

The best solution for advanced industrial applications

MAIN FEATURES

- Fitted with 4 STAINLESS STEEL shear-beam C6 load cells each with 350 Ohm input resistance. OIML R60 approved and protection against dust and immersion according to IP68 standards.
- Stainless steel AISI 304 bearing tubular structure, with removable stainless steel AISI 304 plate and IP67 junction box housing.
- Adjustable, stainless steel shock-proof jointed feet and integrated level.
- 5 m 6-pin shielded cable, complete with female connector.
- Fitted with IP68 connector.
- Up to 15 Vdc power supply.


OPTIONS ONLY AVAILABLE AT TIME OF ORDER

- Calibration with CE-M single or double range approval.
- High resolution models for internal factory use.
- AVAILABLE ON REQUEST: reinforced version for weighing of concentrated loads (coils, forklifts ecc.). Structure in AISI316 stainless steel.

ACCESSORIES

- Column support for weight indicator.
- Frames for flush floor installation.
- Access ramps.
- Models with special sizes and capacities on request.

CONNECTOR PINOUT



Pin	Signal	Color
1	EXC+	Brown
2	EXC-	Grey
3	SENSE-	White
4	SENSE+	Green
5	SIG-	Yellow
6	SIG+	Pink
7		Not connected

OPTIONS FOR ATEX VERSION

- CCATEX: ATEX certificate for each load cell.
- JB4QA: ATEX certified junction box.
- DCATEXMECH: ATEX declaration for the PLATFORM (for the load cells ATEX declaration see CCATEX-1 code). Option to be offered only if the platform is ordered without the indicator, if so, refer to the chosen weight indicator available certifications.

DETAIL 1



DETAIL 2



VERSIONS

Available versions

Codice	l x w x h (mm)	N° celle	Max (kg)	d (g)	M (g)*	M 2R (g)*	d HR (g)*
ETAI3C6	1000x1000x90	4x220kg	300	50	50	--	20
ETAI6C6	1000x1000x90	4x500kg	600	100	100	--	50
ETAI15C6	1000x1000x90	4x500kg	1200	200	200	100-200	100
ETMI3C6	1000x1250x90	4x220kg	300	50	50	--	20
ETMI6C6	1000x1250x90	4x500kg	600	100	100	--	50
ETMI15C6	1000x1250x90	4x500kg	1200	200	200	100-200	100
ETBI3C6	1250x1250x90	4x220kg	300	50	100	--	20
ETBI6C6	1250x1250x90	4x500kg	600	100	100	--	50
ETBI15C6	1250x1250x90	4x500kg	1200	200	200	100-200	100
ETBI30C6	1250x1250x90	4x2000kg	3000	500	500	--	200
ETDI6C6	1250x1500x115	4x500kg	600	100	100	--	50
ETDI15C6	1250x1500x115	4x500kg	1200	200	200	100-200	100
ETDI30C6	1250x1500x115	4x2000kg	3000	500	500	--	200
ETEI6C6	1500x1500x115	4x500kg	600	100	100	--	50
ETEI15C6	1500x1500x115	4x500kg	1200	200	200	100-200	100
ETEI30C6	1500x1500x115	4x2000kg	3000	500	500	--	200
ETFI6C6	1500x2000x130	4x500kg	600	100	100	--	50
ETFI15C6	1500x2000x130	4x500kg	1200	200	200	100-200	100
ETFI30C6	1500x2000x130	4x2000kg	3000	500	500	--	200

WARNING: ETFI model requires special transportation with quoted price.

(g)* : Divisions obtainable only with the relative options, in combination with Dini Argeo weight indicator.

www.diniargeo.com



DINI ARGEO FRANCE sarl	DINI ARGEO GMBH	DINI ARGEO UK Ltd	DINI ARGEO WEIGHING INSTRUMENTS Ltd	DINI ARGEO OCEANIA
France	Germany	United Kingdom	China	Australia

DINI ARGEO
A RICE LAKE WEIGHING SYSTEMS COMPANY

COMPANY HEADQUARTERS
Via Della Fisica, 20
41042 Spezzano di Fiorano Modena • Italy
Tel. +39.0536 843418

SERVICE ASSISTANCE
Via Dell'Elettronica, 15
41042 Spezzano di Fiorano Modena • Italy
Tel. +39.0536 921784

SALES AND TECHNICAL ASSISTANCE SERVICE

All the specifications and images can be subject to variations and upgrades without prior notice.