

## DFWLB

"DFWLB": MULTIFUNCTION IP68 WEIGHT INDICATOR FOR INDUSTRY



Digital weight indicator for industrial environments, easy to install and use. The IP68 protection degree and the built-in long life battery make it particularly suitable for automotive and mobile weighing applications. Standard fitted with a support bracket with adjustable inclination. CE-M approvable (OIML R-76 / EN 45501).

**The best solution  
for advanced industrial  
applications**

## MAIN FEATURES

- 5-key functional waterproof keypad.
- Backlit 25mm LCD display with 6 high contrast digits with icons for showing the active functions.
- Easy to clean ABS IP68 case, resistant to harsh and corrosive environments.
- Suitable for use on the table, column, or wall.
- Fitted with fixing bracket with adjustable inclination.
- A/D 24 bit, 4 channel converter, max. 200 conv./sec. autoselect, and up to 8 signal linearisation points.
- Up to 10.000e or multirange 3 x 3000e @ 0,3  $\mu\text{V/e}$  in CE-M approved versions for legal for trade use.
- Up to 1.000.000 displayable divisions with internal resolution up to 3.000.000 points.
- Connection with up to 8 load cells with input resistance equal to 350 Ohm or up to 16 cells of 700 Ohm each.
- Digital calibration and Set-Up from keypad or from PC through DINITOOLS.
- Power supply through built-in rechargeable battery, with 60h operating time, and fitted with external battery charger (to not use as power adaptor).

## SELECTABLE FUNCTION MODES

- The user can select the operating modes directly using the dedicated key\*:
  - High resolution display x 10
  - Precision weighing with temporary recalibration via a sample weight (for internal factory use)
  - Net/Gross
  - Lb to Kg converter
  - Free conversion factor (for meter and litre counters etc.)
  - Weight totalizer
  - Formulizer
  - +/- controller with quick target and threshold input
  - Percentage weighing
  - Piece counter
  - Hold

The "alibi memory" function is available in combination with the required operating mode and it is activated automatically when installing the relevant optional board.

- Optional functions:
  - PEAK, detection of weight peaks (code DFWPK)
  - Newton to Kg converter (code DFWPK)
- Access to the user menu is gained using the dedicated key\* to adjust the weighing filter, date and time, setpoint and tare weight, which the user can access by entering a programmable access password.

*\* These quick access keys to the menus can be blocked by configuring a dedicated password.*

## MAIN CERTIFICATIONS

- EU Type Examination Certificate (45501:2015)
- OIML R76
- Australian legal for trade certificate of approval (NMI S788)

## I/O SECTION

- RS232/C bidirectional port on RJ11 connector for quick connection (optional RS485) on screw terminal, configurable for PC, PLC, or additional remote display.
- RS232/C bidirectional port configurable for connection to printer or labeller.

## AVAILABLE LANGUAGES FOR PRINTING

- IT, EN, FR, DE, ES, PT, CN\*, EL\*

\* For Chinese and Greek a programming of the printer/labeler is required (S1, only at the time of order)



“YOUR WORLDWIDE PARTNER FOR WEIGHING,”

DINI ARGEO  
FRANCE sarl  
France

DINI ARGEO  
GMBH  
Germany

DINI ARGEO  
UK Ltd  
United Kingdom

DINI ARGEO WEIGHING  
INSTRUMENTS Ltd  
China

DINI ARGEO  
OCEANIA  
Australia



#### COMPANY HEADQUARTERS

Via Della Fisica, 20  
41042 Spezzano di Fiorano Modena • Italy  
Tel. +39.0536 843418

#### SERVICE ASSISTANCE

Via Dell'Elettronica, 15  
41042 Spezzano di Fiorano Modena • Italy  
Tel. +39.0536 921784

SALES AND TECHNICAL ASSISTANCE SERVICE