

MCWN

MCWN "NINJA" SERIES SINGLE SECURITY SUSPENDED CRANE SCALES



Easy to use and reliable professional digital <u>crane</u> <u>scales</u>, for weighing in industrial environments, fitted with protective transport case.

The single security system makes them suitable for lifting and weighing the load.

Thanks to their compact size, these crane scales just slightly reduce the lifting distance of the crane. Available also CE-M APPROVED. Fitted with test certificate obtained with standard weights.

The best solution for advanced industrial applications

MAIN FEATURES

- Single security system, for the lifting and the weighing of the load.
- In compliance with the directives 2006/42 CE, UNI EN 13155/2009, UNI EN 13889, 2014/30/EU.
- Fitted with the following upper and lower shackle:

GR3 for MCWNT1

GR6 for MCWNT3

GR6 for MCWNT6

GR9 for MCWNT9.

- Compact size and minimum distance between upper and lower shackle.
- 25 mm LCD backlit display, easily visible in any lighting condition.
- Precision: +/- 0.03% on MAX.
- 5-key waterproof keypad: Zero, semi automatic or preset Tare, Mode, Print, On/Off.
- Sturdy case in oven-fire painted steel.
- Fitted with infrared remote control for up to 8m distance use. The remote control can be configured by the customer as a single automatic tare or as a remote keypad.
- Power supply:
 - 4 AA batteries included as standard with 40 hour runtime, also compatible with rechargeable AA batteries.
 - Optional internal rechargeable battery kit.
- Digital calibration and programmable Set-Up directly from the keypad or from the PC with Dinitools.
- Programmable digital filter and auto switch-off.
- Operating temperature: -10 /+40 °C.
- RS232 serial port on RJ11 connector for quick programming with Dinitools.
- Fitted with protective transport case with dimensions (WxLxH) 175x480x390mm.

OPTIONS (ONLY AT TIME OF ORDER)

- 2,4 GHz radio interface
- Bluetooth Interface

MAIN FUNCTIONS

- The user can select the operating modes directly using the dedicated key*:
 - High resolution display x 10
 - Precision weighing with temporary recalibration via a sample weight (for internal factory use)
 - Net/Gross
 - Lb to Kg converter
 - Free conversion factor (for meter and litre counters etc.)
 - Weight totalizer
 - Formulizer
 - +/- controller with quick target and threshold input
 - Percentage weighing
 - Percentage batching with programmable target
 - Piece counter
 - Hold
 - PEAK, detection of weight peaks
 - Newton to Kg converter

The "alibi memory" and "setpoint" functions are available in combination with the required operating mode and they are activated automatically when installing the relevant optional board;

- Access to the user menu is gained using the dedicated key* to adjust the weighing filter, date and time, setpoint and tare weight, which the user can access by entering a programmable access password.
 - * These quick access keys to the menus can be blocked by configuring a dedicated password.

DETAIL 1

DETAIL 2





DETAIL 3

DETAIL 4



CODE	WEIGHT (kg)		
	WITHOUT PACKAGING	WITH PACKAGING	
MCWNT1	8	11	
MCWNT3	10	14	
MCWNT6	11	15	
MCWNT9	15	18	

VERSIONS

Available versions Max d						
	Codice	(kg)	(kg)	(kg)		
	MCWNT1-3	300/600/1500	0,1/0,2/0,5			
	MCWNT1M-3 M	1500		0,5		
	MCWNT3-3	600/1500/3000	0,2/0,5/1			
	MCWNT3M-3 M	3000		1		
	MCWNT6-3	1500/3000/6000	0,5/1/2			
	MCWNT6M-3 M	6000		2		
	MCWNT9-3	3000/6000/9500	1/2/5			
	MCWNT9M-3 ™	9000		5		





DINI ARGEO FRANCE sarl France DINI ARGEO GMBH Germany DINI ARGEO UK Ltd United Kingdom DINI ARGEO WEIGHING INSTRUMENTS Ltd China DINI ARGEO OCEANIA Australia



COMPANY HEADQUARTERS

Via Della Fisica, 20 41042 Spezzano di Fiorano Modena - Italy Tel. +39.0536 843418

SERVICE ASSISTANCE

Via Dell'Elettronica, 15 41042 Spezzano di Fiorano Modena - Italy Tel. +39.0536 921784

SALES AND TECHNICAL ASSISTANCE SERVICE