

## JB4QA

"JBQA": ATEX EQUALISED JUNCTION BOX, WITH UP TO 4 LOAD CELLS



IP67 junction box fitted with electronic board for junction and equalisation of 2, 3, or 4 load cells. Terminal boards with a screw for easing the connection of the load cells and the signal adjustment trimmer, for an accurate and reliable equalisation. Marking:  
ATEX II 2G Ex ib IIC T6 Gb for gases.  
ATEX II 2D Ex tb IIIC T115°C Db IP65 for dust.

The best solution  
for advanced industrial  
applications

## TECHNICAL FEATURES

- Case in ABS. Protection degree: IP67.
- Maximum input voltage: 24Vdc.
- Maximum input current: 700mA.
- Maximum input load cell signal: 1000mV.
- Temperature effect: 50ppm/°C.
- Dimensions (lxwxh): 120x80x55mm.



[www.diniargeo.com](http://www.diniargeo.com)

“YOUR WORLDWIDE PARTNER FOR WEIGHING,”

DINI ARGEO  
FRANCE sarl  
France

DINI ARGEO  
GMBH  
Germany

DINI ARGEO  
UK Ltd  
United Kingdom

DINI ARGEO WEIGHING  
INSTRUMENTS Ltd  
China

DINI ARGEO  
OCEANIA  
Australia



#### COMPANY HEADQUARTERS

Via Della Fisica, 20  
41042 Spezzano di Fiorano Modena • Italy  
Tel. +39.0536 843418

#### SERVICE ASSISTANCE

Via Dell'Elettronica, 15  
41042 Spezzano di Fiorano Modena • Italy  
Tel. +39.0536 921784

SALES AND TECHNICAL ASSISTANCE SERVICE