

JB4QA

"JBQA": ATEX EQUALISED JUNCTION BOX, WITH UP TO 4 LOAD CELLS



IP67 junction box fitted with electronic board for junction and equalisation of 2, 3, or 4 load cells. Terminal boards with a screw for easing the connection of the load cells and the signal adjustment trimmer, for an accurate and reliable equalisation. Marking:
ATEX II 2G Ex ib IIC T6 Gb for gases.
ATEX II 2D Ex tb IIIC T115°C Db IP65 for dust.

The best solution
for advanced industrial
applications

TECHNICAL FEATURES

- Case in ABS. Protection degree: IP67.
- Maximum input voltage: 24Vdc.
- Maximum input current: 700mA.
- Maximum input load cell signal: 1000mV.
- Temperature effect: 50ppm/°C.
- Dimensions (lxwxh): 120x80x55mm.



“YOUR WORLDWIDE PARTNER FOR WEIGHING,”

DINI ARGEO
FRANCE sarl
France

DINI ARGEO
GMBH
Germany

DINI ARGEO
UK Ltd
United Kingdom

DINI ARGEO WEIGHING
INSTRUMENTS Ltd
China

DINI ARGEO
OCEANIA
Australia



COMPANY HEADQUARTERS

Via Della Fisica, 20
41042 Spezzano di Fiorano Modena • Italy
Tel. +39.0536 843418

SERVICE ASSISTANCE

Via Dell'Elettronica, 15
41042 Spezzano di Fiorano Modena • Italy
Tel. +39.0536 921784

SALES AND TECHNICAL ASSISTANCE SERVICE