

WKD - 1

"WKD - C4": KIT FOR WEIGHBRIDGES WITH TOUCH-SCREEN INDICATOR



Weighbridges kit made up of 3590ETD touch screen weight indicator with AF03 software for weighbridges, 6 or 8 stainless steel IP68 "RCD" digital load cells, complete with galvanized steel oscillating resting joints and junction box with surge arresters.

Touch screen indicator, specific for weigh bridge.

Junction box with removable terminals and integrated surge arres.

DIGITAL load cells in stainless steel.

CAPACITY: **180t, 240t.**

OIML R60. C4 precision class.

Load cell height **170mm** (including cups height).

"Anti rat" armoured cable for each load cell.

"3590ETD" INDICATOR

- Touch screen, graphic, color display.
- ABS waterproof IP65 case.
- Integrated alibi memory for CE-M approved communication with printer and PC.
- 3 serial ports, 2 RS232 and 1 RS485 for connection to printer, repeater and PC.
- 2 inputs and 4 outputs.
- Power supply unit specifically for digital load cells.
- Protection board for power supply circuit and communication between digital load cells and self-resetting Surge Arresters.
- "AF03" application software suitable for vehicles weighing and weighbridges management, with input/output products check.

To view the full technical data sheet click [HERE](#).

"RCD" digital LOAD CELLS

- C4 (4000 divisions) precision class.
- Made in stainless steel, IP68 protection degree.
- Internal silicone sealing against condensation and temperature changes.
- 30.000 kg max capacity for each load cell.
- 200.000d full load capacity resolution.
- Combined error of Full Scale Output $\pm 0,017\%$
- Operating temperature range $-10^{\circ}\text{C}/+40^{\circ}\text{C}$
- Safe overload 150% F.S.
- "Anti rat" 15 m armoured cable for each cell.
- Self-alignment articulated joints.
- Test certificate available upon request.

"JB10QD" digital JUNCTION BOX

- Junction box with polyester case.
- IP66 protection degree or IP68 with the use of GELBOX anti condensation gel (optional, you need 1200ml of gel).
- Surge Arresters against electric discharges and disturbances.

To view the full technical data sheet click [HERE](#).

DETAIL 1



DETAIL 2



DETAIL 3





DINI ARGEO
FRANCE sarl
France

DINI ARGEO
GMBH
Germany

DINI ARGEO
UK Ltd
United Kingdom

DINI ARGEO WEIGHING
INSTRUMENTS Ltd
China

DINI ARGEO
OCEANIA
Australia



COMPANY HEADQUARTERS

Via Della Fisica, 20
41042 Spezzano di Fiorano Modena • Italy
Tel. +39.0536 843418

SERVICE ASSISTANCE

Via Dell'Elettronica, 15
41042 Spezzano di Fiorano Modena • Italy
Tel. +39.0536 921784

SALES AND TECHNICAL ASSISTANCE SERVICE