DINI ARGEO

A RICE LAKE WEIGHING SYSTEMS COMPANY

SMT

"SMTPLUS": DIRECT AND THERMAL TRANSFER LABELLER



Direct and thermal transfer labeller, connectable to 3590 and CPW indicators. The quick emission of labels, the high printing resolution and the compact size make it suitable for printing in any industrial environment.

The best solution for advanced industrial applications

TECHNICAL FEATURES

- PRINTING METHOD: direct and thermal transfer.
- PRINT RESOLUTION: 8 dots/mm.
- PRINTING SPEED: up to 203 mm/s.
- PRINT MODE: dispensing or strip form.
- MAXIMUM PRINT WIDTH: 108 mm.
- LABEL LENGTH: from 5 mm up to 25400 mm.
- LABEL WIDTH: from 25.4 mm up to 118 mm.
- ROLL SIZE: external diameter up to 203.2 mm.
- THERMAL RIBBON: internal diameter of 25.4 mm, length of 450 metres.
- FONTS: 8, alphanumeric bitmaps, True Type Font.
- USER DISPLAY: 3.5" touchscreen colour HVGA LCD display.
- MEDIA TYPES: die cut labels, tags and continuous strips.
- AVAILABLE BAR CODES:
  - 1D BARCODE: Code 39, Code 93, Code128UCC, Code128 subset A.B.C, Codabar, Interleave 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN e UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, RSS-Stacked, GS1 DataBar, Code 11, China Post.
  - 2D BARCODE: PDF-714, Maxicode, DataMatrix, QR code, Aztec.
- FLASH MEMORY: 128 MB.
- INTERFACES: RS232C (from 1200 to 115200bps),USB 2.0 client and Ethernet.
- STANDARD SOFTWARE PROGRAMMING, for the creation of customised labels with logos, images, weight data, and bar codes.
- SIZE: 248 x 274 x 436 mm (wxhxl).
- WEIGHT: 9.2 kg.
- POWER SUPPLY: 115/230 Vac, 50/60 Hz.
- OPERATING TEMPERATURE: from +5°C to +40°C.
- OPERATING HUMIDITY: from 25% to 85%, non condensing.

WHAT'S NEW COMPARED TO SMTPLUSPRO:

- Small size and robust design:
  - 39% lighter.
  - 30% less bulky.
- Improved printhead:
  - Adjustable printhead pressure.
  - Reinforced printhead hook.
- 3.5" colour touch screen display.
- 32 times the storage capacity for logos and fonts (128 MB).

AVAILABLE ACCESSORIES

- Peel-off kit, with internal automatic rewind.

DETAIL 1



Simple and quick substitution of the roll.

www.diniargeo.com



DINI ARGEO FRANCE sarl	DINI ARGEO GMBH	DINI ARGEO UK Ltd	DINI ARGEO WEIGHING INSTRUMENTS Ltd	DINI ARGEO OCEANIA
France	Germany	United Kingdom	China	Australia

DINI ARGEO
A RICE LAKE WEIGHING SYSTEMS COMPANY

COMPANY HEADQUARTERS
Via Della Fisica, 20
41042 Spezzano di Fiorano Modena • Italy
Tel. +39.0536 843418

SERVICE ASSISTANCE
Via Dell'Elettronica, 15
41042 Spezzano di Fiorano Modena • Italy
Tel. +39.0536 921784

SALES AND TECHNICAL ASSISTANCE SERVICE

All the specifications and images can be subject to variations and upgrades without prior notice.