

KCP50

"KCP50" galvanized steel mounting kit, for CPX/CPA compression load cells



KCP50 is an accessory designed for the correct mounting and operation of CPA and CPX series compression load cells under silos, hoppers and tanks (up to 50t per support point).

KCP50 offers a correct protection against overloads and side forces and actively contributes to the protection against accidental tipping of the silo.

Available in EN 1090 certified version.

Available in ATEX version for zones 1&21, 2&22.

**The best solution
for advanced industrial
applications**

TECHNICAL FEATURES

- Designed for mounting 30t CPX and 20 to 50t CPA load cells
- Zinc-plated steel construction (stainless steel by quote)
- Protects against tipping, withstanding forces up to 130KN
- Self-aligning system designed to allow mechanical expansion of the structure while maintaining weighing precision
- Locking screws and bypass for completely safe load cell maintenance.
- Total weight of the kit (without load cell): 28kg with stay rod, 27kg without stay rod.
- Optional lateral stay rod available, particularly suitable to counter lateral disturbing forces in dynamic applications (e.g. mixers).

	Protection	Force (KN)
↕	Max lift-off force	130
↔	Max side force	100

DETAIL 1





DINI ARGEO
FRANCE sarl
France

DINI ARGEO
GMBH
Germany

DINI ARGEO
UK Ltd
United Kingdom

DINI ARGEO WEIGHING
INSTRUMENTS Ltd
China

DINI ARGEO
OCEANIA
Australia



COMPANY HEADQUARTERS

Via Della Fisica, 20
41042 Spezzano di Fiorano Modena • Italy
Tel. +39.0536 843418

SERVICE ASSISTANCE

Via Dell'Elettronica, 15
41042 Spezzano di Fiorano Modena • Italy
Tel. +39.0536 921784

SALES AND TECHNICAL ASSISTANCE SERVICE