

TE-69K

NEW TE 69K SERIES SINGLE-CELL PLATFORMS



AISI 304 Stainless Steel. Load cell in Stainless Steel. IP68 and IP69K protection rating.

Precision class C3, C3MR, C3MI, C6, C6MR.

TE 69K series platforms are known for their accuracy and robustness.

The AISI 304 stainless steel construction and IP68 and IP69K load cell protection make these platforms ideal for industrial and commercial applications in harsh environments with high humidity and water exposure.

The C6 accuracy class approved load cell provides accurate weighing to improve production quality and optimize raw material consumption.

ENVIRONMENT: WET, CORROSIVE

The best solution
for advanced industrial
applications

MAIN FEATURES

- Functions with an approved "single point" STAINLESS STEEL C6 load cell according to OIML R60 standards with protection against dust and water splashes according to IP68 and IP69K standards.
- Structure with tubulars, mechanics, trinkets and loading surface in AISI304 satin finish stainless steel.
- Fitted with adjustable STAINLESS steel feet with plastic resting surface and level.
- Up to 15 Vdc power supply.
- Shielded 3m connection cable with connectors for connection to the indicator.
- Available in approved multi-range 3000+3000e or 6000+6000e, and multi-interval 2x3000e.
- Made in Italy.

AVAILABLE UPON PRICE ESTIMATE

- Special sizes and capacities.
- ATEX or IECEX version.

Multi Interval Version "-MI"

- The T and TE series scales are available in a 2x3000e multi-range approved version, the best combination of accuracy and ease of use for a class C3 approved weighing instrument.

Compared to the more common multi-range type approval, the multi-interval type approval offers ADAPTIVE measurement resolution, which automatically varies by adjusting to the weight being measured.

NOTE: Multi-interval models are distinguished by the final "-MI" abbreviation and must be paired with a DFW or 3590 series Dini Argeo indicator, DiniCal calibration service and ECEM2MI approval service.

VERSIONS

Available versions

Codice	l x w x h (mm)	Max (kg)	d (g)	 (g)*	d HR (g)*
TSE3-69K	230x330x90	3	0,5	See table below	0,2
TSE3-69K-MI	230x330x90	3	--	0,5/1 (Multi interval)	--
TSE6-69K	230x330x90	6	1	See table below	0,5
TSE6-69K-MI	230x330x90	6	--	1/2 (Multi interval)	--
TSE12-69K-MI	230x330x90	12	--	2/5 (Multi interval)	--
TSE15-69K	230x330x90	15	2	See table below	1
TTE6-69K	330x330x90	6	1	See table below	0,5
TTE6-69K-MI	330x330x90	6	--	1/2 (Multi interval)	--
TTE12-69K-MI	330x330x90	12	--	2/5 (Multi interval)	--
TTE15-69K	330x330x90	15	2	See table below	1
TTE30-69K	330x330x90	30	5	See table below	2
TTE30-69K-MI	330x330x90	30	--	5/10 (Multi interval)	--
TQE12-69K-MI	400x400x115	12	--	2/5 (Multi interval)	--
TQE15-69K	400x400x115	15	2	See table below	1
TQE30-69K	400x400x115	30	5	See table below	2
TQE30-69K-MI	400x400x115	30	--	5/10 (Multi interval)	--
TQE60-69K	400x400x115	60	10	See table below	5
TQE60-69K-MI	400x400x115	60	--	10/20 (Multi interval)	--
TME30-69K	400x500x115	30	5	See table below	2
TME30-69K-MI	400x500x115	30	--	5/10 (Multi interval)	--
TME60-69K	400x500x115	60	10	See table below	5
TME60-69K-MI	400x500x115	60	--	10/20 (Multi interval)	--

(*) Divisions obtainable only with the relative options, in combination with Dini Argeo weight indicator.



DINI ARGEO
FRANCE sarl
France

DINI ARGEO
GMBH
Germany

DINI ARGEO
UK Ltd
United Kingdom

DINI ARGEO WEIGHING
INSTRUMENTS Ltd
China

DINI ARGEO
OCEANIA
Australia



COMPANY HEADQUARTERS

Via Della Fisica, 20
41042 Spezzano di Fiorano Modena • Italy
Tel. +39.0536 843418

SERVICE ASSISTANCE

Via Dell'Elettronica, 15
41042 Spezzano di Fiorano Modena • Italy
Tel. +39.0536 921784

SALES AND TECHNICAL ASSISTANCE SERVICE