

TPWI-PRO-EX3GD

TPWI-PRO series "EX" 3GD PALLET TRUCK SCALE IN
STAINLESS STEEL ZONE 2/22



AISI 304 stainless steel pallet truck scale for use in ATEX hazardous areas 2 & 22, with Ex II 3G IIC T6 Gc X and Ex II 3D IIC T115C° Dc X protection. Also available in approved version for legal-for-trade use.

Made, calibrated and adjusted in Italy by Dini Argeo, using certified sample weights.

**The best solution
for advanced industrial
applications**

WEIGHING FEATURES

- Maximum lifting capacity: 2.000 kg; special capacities on request, up to 3.000 kg.
- Resolution:
 - > internal use: 0,2 / 0,5 kg
 - > approved: 0,5 / 1 kg
- Accuracy (weighing of goods on Europallet with distributed load):
 - > internal use: +/- 1 kg
 - > approved: according to CE certification (Directive 2014/31/EU)
- Calibration and Set-Up parameters configurable from keyboard or PC.

WHY CHOOSE TPWI-PRO serie EX 3GD

- Pallet truck scale with thick stainless steel structure, entirely manufactured in Italy.
- Lifting pump manufactured entirely in Italy, available on request for lifting up to 3.000 kg.
- Made with ATEX certified components.
- Can send weight data to devices in a safe area thanks to wireless transmission options.
- Weight indicator with waterproof casing in IP68 stainless steel, easy to clean and resistant in harsh and corrosive environments.
- The large backlit 25 mm LCD display makes it easier to read even in low light conditions.
- Available in approved version for legal-for-trade use.
- Extractable battery, rechargeable in safe area, connectable and disconnectable to the weighing system also in hazardous area.
- Autonomy of about 100 hours, or 24/7 with optional second rechargeable battery.
- Built with 4 Dini Argeo load cells, ATEX certified, in IP68 stainless steel.
- Each pallet truck is tested and supplied with a calibration certificate to guarantee the declared accuracy.
- Special non-standard dimensions available on estimate.

TECHNICAL FEATURES

- Low-profile forks, only 85 mm.
- Fork dimensions 1150 x 550 x 85 mm.
- Lifting range: from 85 to 205 mm.
- Pallet truck weight: 135 kg approx.
- Supporting structure made entirely of extra-thick AISI 304 stainless steel.
- Forks in AISI 304 stainless steel.
- Closed fork covers for increased protection of the double load wheels.
- Antistatic guide wheels, with polyurethane coating for smooth running. 200 mm diameter ensures optimum smoothness and manoeuvrability.
- Antistatic loading rollers.
- Lifting pump in AISI 304 stainless steel allowing controlled lowering of the forks.
- Waterproof membrane keyboard, with 17 numeric/functional keys.
- Dini Argeo electronics, ATEX certified, intrinsically safe.
- Standard 110/230Vac 50Hz battery charger with EU, UK, US and AU plugs (recharge time 8 hours).
- Temperature range: -10° / +40° C

THE EASIEST ONE TO RECALIBRATE AND REPAIR

- The only one without junction box: the adjustment of each single load cell is conveniently carried out from the keyboard.
- Spare parts and wearing parts always available and ready for delivery.
- Specialized service centers throughout Italy.

MAIN FUNCTIONS

- Zeroing, Tare, Printing (only in safe zone).
- High resolution display x 10.
- Net/Gross or lb/kg conversion.
- Weights totalisation, Formulation.
- +/- control.
- Percentage weighing.
- Counting (Max. counting resolution 1.500.000 divisions).
- Set Point Control (with optional interface).

OTHER AVAILABLE VERSIONS

- Other capacities / special resolutions: upon request.
- Other special versions: upon request.

TAILORED SIZES FOR EVERY NEED

- TPWI-PRO "EX" 3GD can be manufactured with special fork dimensions:
 - Lengths from 800 up to 2200 mm (up to 1800 mm in approved version)
 - Widths from 400 up to 900 mm (up to 680 mm in approved version)



DETAIL 1



Extractable battery

VERSIONS

Available versions

	Codice	Max (kg)	d (kg)	M (kg)
	TPWI-PRO-EX3GD	1000 / 2000	0,2 / 0,5	--
	TPWIM-PRO-EX3GD M	1000 / 2000	--	0,5 / 1



www.diniargeo.com

“YOUR WORLDWIDE PARTNER FOR WEIGHING,”

DINI ARGEO
FRANCE sarl
France

DINI ARGEO
GMBH
Germany

DINI ARGEO
UK Ltd
United Kingdom

DINI ARGEO WEIGHING
INSTRUMENTS Ltd
China

DINI ARGEO
OCEANIA
Australia



COMPANY HEADQUARTERS

Via Della Fisica, 20
41042 Spezzano di Fiorano Modena • Italy
Tel. +39.0536 843418

SERVICE ASSISTANCE

Via Dell'Elettronica, 15
41042 Spezzano di Fiorano Modena • Italy
Tel. +39.0536 921784

SALES AND TECHNICAL ASSISTANCE SERVICE