DINI ARGEO

A RICE LAKE WEIGHING SYSTEMS COMPANY

PROFI232

"PROFI232" EXTERNAL PROFIBUS INTERFACE IN CASE FOR DIN BAR, FOR "ENTERPRISE" SERIES INDICATORS



External interface which allows to connect the CPWE and 3590E weight indicators to the Profibus networks. Wide range of available data.

The best solution for advanced industrial applications

FUNCTIONING

- Complete functionality from the Profibus-DP Slave, in according to IEC 61158
- 16 input bytes / 16 bytes output on SSC interface
- Automatic baud rate selection: from 9600 bit/s to 12Mbit/s
- Wide range of available data depending on the weight indicator to which it is applied
- Available for CPWE and 3590E indicators, in the versions with management of the Profibus protocol

TECHNICAL FEATURES

- ABS case for panel mounting on DIN bar
- Dimensions lxwxh (mm): 53 x 58 x 90
- Power supply: from 12 to 24Vdc
- RS232 and RS485 serial ports on terminal board
- Profibus port on 9 Pin connector
- Board optoisolation against electric or electrostatic discharges

www.diniargeo.com



DINI ARGEO FRANCE sarl	DINI ARGEO GMBH	DINI ARGEO UK Ltd	DINI ARGEO WEIGHING INSTRUMENTS Ltd	DINI ARGEO OCEANIA
France	Germany	United Kingdom	China	Australia

DINI ARGEO
A RICE LAKE WEIGHING SYSTEMS COMPANY

COMPANY HEADQUARTERS
Via Della Fisica, 20
41042 Spezzano di Fiorano Modena • Italy
Tel. +39.0536 843418

SERVICE ASSISTANCE
Via Dell'Elettronica, 15
41042 Spezzano di Fiorano Modena • Italy
Tel. +39.0536 921784

SALES AND TECHNICAL ASSISTANCE SERVICE

All the specifications and images can be subject to variations and upgrades without prior notice.