

AWT20L

AWT20L SERIES WEIGHT TRANSMITTER



Weight transmitter with 0-20mA, 4-20mA, 0-10Vdc or +/- 5Vdc analogue output at choice. Suitable for assembling on the panel rear or in tin box on omega bar. Normally used with 12-bit analogue / digital cards installed on PLC

**The best solution
for advanced industrial
applications**

MAIN FEATURES

- Analogue filter for reducing the weight oscillations by adjusting the trimmer one turn.
- Dimensions 113 x 93 mm, height 60 mm
- Coarse zero through 4 dip-switches from –2,4 to 17 mV
- Coarse full scale through 4 dip-switches from 2 to 24 mV
- Fine zero through 10-turn trimmer, 15% of field
- Fine full scale through 10-turn trimmer, 15% of field
- Power supply from 20 to 28 Vdc – Power absorbed 6VA.
- Accuracy 0,25% of full scale output F.S.
- Non-repeatability 0,01% F.S.
- Thermal stability 0,01% F.S. /10°C
- Operating temperature from –10 to + 50°C

I/O SECTION

- Measuring range from 3,5 to 24 mV
- Load cell supply 10 Vdc
- Connection up to 6 load cells with 350 Ohm input resistance.
- 0-20mA, 4-20 mA or 0-10V analogue output at choice. Alternatively, +/-5Vdc output (only AWT20L-5 model)



www.diniargeo.com

“YOUR WORLDWIDE PARTNER FOR WEIGHING,”

DINI ARGEO
FRANCE sarl
France

DINI ARGEO
GMBH
Germany

DINI ARGEO
UK Ltd
United Kingdom

DINI ARGEO WEIGHING
INSTRUMENTS Ltd
China

DINI ARGEO
OCEANIA
Australia



COMPANY HEADQUARTERS

Via Della Fisica, 20
41042 Spezzano di Fiorano Modena • Italy
Tel. +39.0536 843418

SERVICE ASSISTANCE

Via Dell'Elettronica, 15
41042 Spezzano di Fiorano Modena • Italy
Tel. +39.0536 921784

SALES AND TECHNICAL ASSISTANCE SERVICE