

3590EBOX

SELF-SERVICE SYSTEM FOR WEIGHBRIDGES



Self-service system for weighbridge management, complete with 3590E weight indicator and thermal printer, integrated in a sturdy stainless steel case. The badge reader, RFID reader, or programmable coin acceptor, are available depending on the model. CE-M approvable.

TECHNICAL FEATURES

- Satin stainless steel sturdy case, complete with electromechanical and power supply unit for integrated devices.
- Sheet steel protection visor against sun and rain.
- 3590E weight indicator fitted with:

Red led 15mm display and backlit LCD graphic 25x100mm display.

25-key alphanumerical waterproof keyboard.

Synoptic with 16 bright LEDs showing the active functions.

- Fitted with alibi memory.
- Thermal printer fitted with paper cutter. Print speed >50mm/sec., 203 dpi resolution, 24/40 columns, 60mm paper width.
- Badge reader integrated in the 3590EBOXBDG version.
- Integrated coin acceptor, standard programmed for using with Euro coins (no change given), complete with a built-in collection container (3590EBOXGET version).
- RFID reader integrated in the 3590EBOXRFID version, with a reading capacity of about 30mm distance.
- 230Vac power supply.

MAIN CERTIFICATIONS

- EU Type Examination Certificate (45501:2015)
- OIML R76
- OIML R134 (AF09)

MAIN FUNCTIONS

- · Clearing, Automatic Tare, Presettable Tare, locked, unlocked tare.
- Management of the main digital load cells available on the market.
- Automatic acquisition of the operator and vehicle data, through magnetic badge, for storage of input/output weighs.
- Management of vehicles with trailer also on 2 scales (tractor is weighed on scale 1 + trailer is weighed on scale 2)
- Database of 500 customers/suppliers with two alphanumeric descriptions of 20 characters, input and output total, net total, weighs total.
- Database of 500 articles with alphanumeric description of 20 characters, input total, output total, net total, weighs total.
- Database of 500 vehicles with alphanumeric description of 20 characters, plate (10 crt), linked tare, input total, output total, net total, weighs total.
- 6 levels of totals zeroable and printable in an independent way: partial total, general total, grand total, customer total, article total, vehicle total.
- Printing of complete database reports or just the handled articles.
- Automatic printing with completely configurable layout.
- Possibility to set a password to access the SETUP.









DINI ARGEO FRANCE sarl France DINI ARGEO GMBH Germany

DINI ARGEO UK Ltd United Kingdom DINI ARGEO WEIGHING INSTRUMENTS Ltd China DINI ARGEO OCEANIA Australia



COMPANY HEADQUARTERS

Via Della Fisica, 20 41042 Spezzano di Fiorano Modena - Italy Tel. +39.0536 843418

SERVICE ASSISTANCE

Via Dell'Elettronica, 15 41042 Spezzano di Fiorano Modena - Italy Tel. +39.0536 921784

-	
	SALES AND TECHNICAL ASSISTANCE SERVICE