

JBQAI

"JBQAI": EQUALISED JUNCTION BOX FOR ATEX ENVIRONMENTS, WITH UP TO 4 LOAD CELLS



Stainless steel junction box with IP66 protection from water and dust, and fitted with an intrinsically safe electronic board for junction and equalisation of load cells. Terminal boards with screws for easing the connection of the load cells and signal adjustment trimmer, for an accurate and reliable equalisation. Marking: ATEX II 2G Ex ib IIC T6 Gb for gases. ATEX II 2D Ex tb IIIC T115°C Db IP65 for dust.

The best solution
for advanced industrial
applications

TECHNICAL FEATURES

- Designed and made according to the ATEX directive, group II category 2GD, according to the IEC/EN60079-0, IEC/EN60079-11, and IEC/EN60079-31 norms.
- Stainless steel case.
- PG9 metallic cable gland.
- Protection degree: IP66.
- Dimensions: 190x130x45mm (lxwxh).

NOTE: the dimensions are not compatibles for mounting on 4 load cells platforms/pallet weighers.

ATEX PARAMETERS OF THE JUNCTION BOX

- $U_o = U_i = 24V_{dc}$
- $I_o = I_i = 174mA$
- $C_o = C_i = 0mF$
- $L_o = L_i = 0mH$

or

- $U_o = U_i = 12V_{dc}$
- $I_o = I_i = 3,33A$
- $C_o = C_i = 0mF$
- $L_o = L_i = 0mH$



DINI ARGEO
FRANCE sarl
France

DINI ARGEO
GMBH
Germany

DINI ARGEO
UK Ltd
United Kingdom

DINI ARGEO WEIGHING
INSTRUMENTS Ltd
China

DINI ARGEO
OCEANIA
Australia



COMPANY HEADQUARTERS

Via Della Fisica, 20
41042 Spezzano di Fiorano Modena • Italy
Tel. +39.0536 843418

SERVICE ASSISTANCE

Via Dell'Elettronica, 15
41042 Spezzano di Fiorano Modena • Italy
Tel. +39.0536 921784

SALES AND TECHNICAL ASSISTANCE SERVICE