

# PLX1K

"PLX1K-1" SERIES' 1000 Ohm LOAD CELL KITS FOR ASSEMBLING FLOOR SCALES



Ideal for creating platforms with 4 load cells of various sizes and capacities. The kit is made up of 4 1000 Ohm IP68 stainless steel load cells, OIML approved, together with adjustable stainless steel resting feet and an equalisation box.

## **LOAD CELL TECHNICAL FEATURES**

- · C3 precision class
- Made in stainless steel with laser welding
- IP68 protection against dust and water.
- Capacities from 500 to 2000 kg (for each cell)
- Minimum load cell verification interval: Vmin = EMax / 10.000
- Maximum number of verification intervals: nLC = 3000
- Combined error: 0,017% of Full Scale Output (F.S.)
- Full Scale Output: 2mV/V +/- 0.5%
- Temperature effect on zero: 0,002% /°C
- Temperature effect on full scale output: 0,002% /°C
- Compensated Temperature Range: -10°C/+50°C
- Operating Temperature Range: -20°C/+60°C
- Creep error after 30 minutes: 0,02% F.S.
- Maximum tolerated excitation voltage: 15 Vdc
- Input Resistance: 1100 ± 20 Ohm
  Output Resistance: 1000 ± 20 Ohm
- Insulation Resistance: >5000 MOhm
- Safe Overload: 150% F.S.
- Ultimate Overload: 300% F.S.
- 6-wire shielded cable, 5m long, 5 mm diameter

### **RESTING FEET**

- Adjustable in height
- Structure in STAINLESS steel
- Anti-slip base
- Ipersanitizable
- Fitted with locking bush

## **JUNCTION BOX**

- Built-in junction and equalisation board
- IP67 protection from dust and water
- 5 PG9 Cable glands

IN +	BROWN
IN -	GREEN
SIG (OUT) +	YELLOW
SIG (OUT) -	WHITE
SENSE+	GRAY
SENSE -	ROSE
SHIELD	METAL





DINI ARGEO FRANCE sarl France DINI ARGEO GMBH Germany

DINI ARGEO UK Ltd United Kingdom DINI ARGEO WEIGHING INSTRUMENTS Ltd China DINI ARGEO OCEANIA Australia



#### **COMPANY HEADQUARTERS**

Via Della Fisica, 20 41042 Spezzano di Fiorano Modena - Italy Tel. +39.0536 843418

#### SERVICE ASSISTANCE

Via Dell'Elettronica, 15 41042 Spezzano di Fiorano Modena - Italy Tel. +39.0536 921784

-	
	SALES AND TECHNICAL ASSISTANCE SERVICE