

DFWATEX3GD

DFW "ATEX3GD": WEIGHT INDICATOR FOR ATEX 2 & 22 ZONES



Weight indicator for areas classified as hazardous with protection methods according to:

ATEX II 3G Ex nR IIC T6 Gc X for gases

ATEX II 3D Ex tc IIIC T85°C Dc IP68 X for dust.

Ideal for creating weighing systems, batching, and automation systems. CE-M approvable (OIML R-76 / EN 45501).

**The best solution
for advanced industrial
applications**

MAIN FEATURES

- Waterproof 17-key functional keypad.
- Backlit LCD display with 6 25-mm high contrast digits and with indication of active functions.
- IP68 Satin finish stainless steel case.
- Suitable for use on the table, or wall.
- Dimensions: 264x174x115mm.
- Up to 10.000e or multirange 3 x 3000e @ 0,3 $\mu\text{V/e}$ in CE-M approved version for legal for trade use.
- Up to 1.000.000 displayable divisions for internal factory use.
- Up to 8 signal linearization points with DINITOOLS (3 from keypad).
- Internal resolution up to 3.000.000 points.
- A/D 24-bit sigma-delta conversion, up to 200 conv./sec. autoselect.
- Board protection case inside the box.
- Digital calibration and set-up from keyboard.
- Instrument management & configuration from PC with DINITOOLS.
- 4 channels (for single weighing system).
- Power supply:
 - DFWATEX3GD: through 110-240Vac internal power adapter (optional power supply cable);
 - DFWATEX3GDB: through optional external battery (BP6ESTATEX3GD code), rechargeable in safe area. Battery charger not included.
- Connection with up to 8 load cells with 350 Ohm input resistance.

MAIN CERTIFICATIONS

- EU Type Examination Certificate (45501:2015)
- OIML R76
- Australian legal for trade certificate of approval (NMI S788)

I/O SECTION

- RS232/C port configurable for connection to printer/labeller in safe zone.
- RS232/C (or optionally RS485) bi-directional port configurable for PC, PLC, additional remote display, in safe zone.

FUNCTIONS

- **KEYBOARD:**
Zeroing, Automatic tare, Presettable tare, printing and/or data transmission, selectable function command, on/off switching, database of 20 tares, 2 Numeric IDs, keyboard lock, repetition of last printout made.
- **SELECTABLE FUNCTIONS:**
 - High Resolution Weighing x 10.
 - Net/Gross or lb/kg conversion.
 - Accumulation.
 - Formula weighing.
 - +/- Checkweighing.
 - Percentage weighing.
 - Approved transmission of the weight to PC/PLC (with Alibi memory ALMEM option).
 - Counting(Max. resolution of 1.500.000 divisions).
 - In/Out Truck weighing.
 - Hold.
 - Set Point Control (with DFIO option).

MASTER/REPEATER OPTION

- Specific programme (MSTSLV code) for use of the indicator as a universal weight repeater or as a multi-scale repeater (MASTER) in combination with DFW/DGT/MCW.
FUNCTIONING MODES:
- Multi-scale repeater (MASTER)
function which allows to repeat up to 32 independent scales, with the possibility of managing their functions, or displaying and printing the sum of the weighs of all the scales.
- UNIVERSAL weight repeater
function which allows to repeat the weight of any scales, through the configuration of the input string.
- [Click to learn more.](#)

AVAILABLE UPON PRICE ESTIMATE

- 24 Vdc power supply.

AVAILABLE LANGUAGES IN PRINTING

- IT, EN, FR, DE, ES, PT, CN*, EL*

* For Chinese and Greek a programming of the printer/labeler is required (S1, only at the time of order)



DINI ARGEO
FRANCE sarl
France

DINI ARGEO
GMBH
Germany

DINI ARGEO
UK Ltd
United Kingdom

DINI ARGEO WEIGHING
INSTRUMENTS Ltd
China

DINI ARGEO
OCEANIA
Australia



COMPANY HEADQUARTERS

Via Della Fisica, 20
41042 Spezzano di Fiorano Modena • Italy
Tel. +39.0536 843418

SERVICE ASSISTANCE

Via Dell'Elettronica, 15
41042 Spezzano di Fiorano Modena • Italy
Tel. +39.0536 921784

SALES AND TECHNICAL ASSISTANCE SERVICE