

WBKPTD

"WBKPTD - C4": DIGITAL KIT FOR WEIGHBRIDGES



Kit for weighbridges made up of 8 RCPTD series IP68 stainless steel digital load cells, complete with galvanized steel oscillating resting joints and 10 input junction box (available for 3590E TOUCH SCREEN indicator).

Special alloy steel body with stainless steel external casing; manufactured with laser solderings.

TOTAL CAPACITY : 240t (8 x 30t cells)

OIML R60, C4 precision class

Load cell height 200mm (including cups height).

Load cells connection cable length: 18m.

**The best solution
for advanced industrial
applications**

LOAD CELL FEATURES

- Special alloy steel body with stainless steel external casing; manufactured with laser solderings.
- IP68 protection rating.
- Capacity 30000kg.
- Fitted with self-aligned articulated joints, self-centering plates and protection washer.
- Shielded 18m connection cable.
- Test certificate available upon request.
- Approved with 3590E touch screen indicator for legal-for-trade use.

To view the full technical data sheet click [HERE](#).

JUNCTION BOX FEATURES

- 10 input JB10QD junction box with reinforced polyester case.
- IP66 protection rating or IP68 protection with GELBOX option.
- Surge Arresters against electric discharges and disturbances.

To view the full technical data sheet click [HERE](#).



DINI ARGEO
FRANCE sarl
France

DINI ARGEO
GMBH
Germany

DINI ARGEO
UK Ltd
United Kingdom

DINI ARGEO WEIGHING
INSTRUMENTS Ltd
China

DINI ARGEO
OCEANIA
Australia



COMPANY HEADQUARTERS

Via Della Fisica, 20
41042 Spezzano di Fiorano Modena • Italy
Tel. +39.0536 843418

SERVICE ASSISTANCE

Via Dell'Elettronica, 15
41042 Spezzano di Fiorano Modena • Italy
Tel. +39.0536 921784

SALES AND TECHNICAL ASSISTANCE SERVICE