

JB4QIP69K

"JB4QIP69K": EQUALISED JUNCTION BOX WITH 4 INPUTS, IN STAINLESS STEEL WITH IP68/IP69K PROTECTION



AISI 304 stainless steel junction box with IP68/IP69K protection from water and dust, fitted with electronic board for junction and equalisation of 4 load cells.

Equalisation board with signal adjustment trimmer, for an accurate and reliable equalisation.

The reversible fixing bracket allows the junction box to be hung on the wall, thus saving space.

TECHNICAL FEATURES

- AISI 304 stainless steel case (AISI 316 upon request)
- Protection rating: IP68/IP69K
- IP69K standard anti-condensation valve
- Metallic cable glands
- Maximum input voltage: 24Vdc
- Maximum input current: 700mA
- Maximum input load cell signal: 1000mV
- Temperature effect: 50ppm/°C
- 4 cell inputs on screw connector
- Dimensions: 221x105x39mm (lxwxh)
- NOTE: available in ATEX version upon request.

Other

- Easy to sanitize with water jets
- Adjustable height to increase cleaning space





DINI ARGEO FRANCE sarl France DINI ARGEO GMBH Germany

DINI ARGEO UK Ltd United Kingdom DINI ARGEO WEIGHING INSTRUMENTS Ltd China DINI ARGEO OCEANIA Australia



COMPANY HEADQUARTERS

Via Della Fisica, 20 41042 Spezzano di Fiorano Modena - Italy Tel. +39.0536 843418

SERVICE ASSISTANCE

Via Dell'Elettronica, 15 41042 Spezzano di Fiorano Modena - Italy Tel. +39.0536 921784

-	
	SALES AND TECHNICAL ASSISTANCE SERVICE