

## LCCB

"LCCB": CABLE for CONNECTION TO LOAD CELLS



Shielded cable for connection of weight indicators to load cells or junction boxes.

The best solution  
for advanced industrial  
applications

## LCCB cable features

- Type: 6 x 0,25 mm<sup>2</sup>, 5,5mm diameter.
- Built-in shielding for protection from disturbances.

<u>Dini Argeo standard of colour codes</u>	
<u>Colour</u>	<u>Function</u>
YELLOW	OUTPUT -
PINK	OUTPUT +
GREEN	SENSE +
WHITE	SENSE -
BROWN	INPUT +
GREY	INPUT -

## LCCBA cable features

- Armoured cable, transparent PVC outer sheath.
- Type: 6 x 0,25 mm<sup>2</sup>, 8 mm diameter.
- Built-in shielding for protection from disturbances.

<u>Dini Argeo standard of colour codes</u>	
<u>Colour</u>	<u>Function</u>
YELLOW	OUTPUT -
PINK	OUTPUT +
GREEN	SENSE +
WHITE	SENSE -
BROWN	INPUT +
GREY	INPUT -

## LCCBM cable features

- Indicated for applications with moving cables.
- Type: 4 x 0,34 mm<sup>2</sup>.
- Built-in shielding for protection from disturbances.

Dini Argeo standard of colour codes	
<i>Colour</i>	<i>Function</i>
YELLOW	OUTPUT -
GREEN	OUTPUT +
WHITE	INPUT -
BROWN	INPUT +

### DETAIL 1



### DETAIL 2



shielded 4-pole cable for load cells

LCCBA: Armoured cable 6x0.25 mm<sup>2</sup>



[www.diniargeo.com](http://www.diniargeo.com)

“YOUR WORLDWIDE PARTNER FOR WEIGHING,”

DINI ARGEO  
FRANCE sarl  
France

DINI ARGEO  
GMBH  
Germany

DINI ARGEO  
UK Ltd  
United Kingdom

DINI ARGEO WEIGHING  
INSTRUMENTS Ltd  
China

DINI ARGEO  
OCEANIA  
Australia



#### COMPANY HEADQUARTERS

Via Della Fisica, 20  
41042 Spezzano di Fiorano Modena • Italy  
Tel. +39.0536 843418

#### SERVICE ASSISTANCE

Via Dell'Elettronica, 15  
41042 Spezzano di Fiorano Modena • Italy  
Tel. +39.0536 921784

SALES AND TECHNICAL ASSISTANCE SERVICE